



## HIDE 12.5" DRAIN COVER FLOW RATE GUIDE: SLOT WIDTH 0.197 IN = 17.8GPM

### TECHNICAL EXPLANATION (US UNITS):

The flow capacity of a slot drain depends on the slot's cross-sectional area and the hydraulic conditions (slope/grade, surface roughness, and available head). For this estimate, we use a standard reference flow for a known slot width and scale proportionally by slot width. For project-specific design, apply open-channel hydraulics (e.g., Manning) or consult a drainage engineer.

### HDC12.5 FLOW RATE:

Given

Slot width,  $W = 0.197$  in

Total slot length around cover,  $L = 1,256$  mm  $\approx 49.45$  in = 4.121 ft  
(corresponds to four sides of  $\sim 12.36$  in each; 12.5 in square cover)



#### 1. Cross-Sectional Area

$$A=W \times L$$

$$A=0.197 \text{ in} \times 49.45 \text{ in} \approx 9.74 \text{ in}^2$$

#### 2. Reference Flow

A 1/2-inch (0.50 in) wide slot conveys  $\approx 11.0$  GPM per foot of slot length under typical conditions.

#### 3: Total Flow Rate:

$$\text{Width ratio: } 0.197/0.50=0.3937$$

$$\text{Flow per foot for 0.197 in slot: } 11.0 \text{ GPM/ft} \times 0.3937 \approx 4.33 \text{ GPM/ft}$$

$$\text{Total flow for } L=4.121 \text{ ft: } 4.33 \text{ GPM/ft} \times 4.121 \text{ ft} \approx 17.8 \text{ GPM}$$

#### 4: (US hydraulic form)

$$17.8 \text{ GPM} \approx 0.0398 \text{ cfs}$$

(Using 1 cfs=448.83 GPM.)

### Guide Flow Rate:

For the 12.5 in Drain ( $\approx 12.36$  in) Square HIDE Drain Cover with a 0.197 in slot, the estimated capacity is  $\approx 17.8$  GPM ( $\approx 0.0398$  cfs) under typical hydraulic conditions.

### Disclaimer:

This figure is a general guide. Actual performance varies with installation specifics such as slope/grade, surface roughness, inlet conditions, headwater depth, and site hydraulics. For exact sizing and compliance, perform project-specific calculations or consult a licensed drainage/civil engineer.